


PACKUNGEN

Material: Nitril-gummi 80 NBR/99018





Besonders geeignet für Wasser ÷ 30° + 100° C.

(auch geeignet für Öl)

FÜR SCHLAUCHVERSCHRAUBUNG

	DYROS-NR:	BESCHREIBUNG:	A	B
<u>Dicke 2 mm</u>				
	518	1/2"	Ø 18	Ø 12,8
	523	3/4"	Ø 23	Ø 17,2
	530	1"	Ø 30	Ø 23,4
	538	1 1/4"	Ø 38	Ø 29,0
	544	1 1/2"	Ø 44	Ø 34,0
	556	2"	Ø 56	Ø 45,0

FÜR WASSER KUPPLUNGEN UND ÜBERGANGSLIED

	DYROS-NR:	BESCHREIBUNG:	A	B
<u>Dicke 2,5 mm</u>				
	509	22 x 1	Ø 21,2	Ø 13,0
<u>Dicke 3 mm</u>				
	501	1/2"	Ø 19,2	Ø 11,0
	503	3/4"	Ø 24,5	Ø 15,5
	507	7/8"	Ø 28,3	Ø 20,0
<u>Dicke 4 mm</u>				
	511	1"	Ø 30,6	Ø 21,0
<u>Dicke 7 mm</u>				
	501G	1/2"	Ø 19,2	Ø 11,0